

Connections & Drive



Connectors

2 × 4-point speaker connector

Recommended controller

Compatible amplified controller with dedicated presets.

System control

Linearization, protection and optimization are handled by compatible drive electronics.

Deployment

Designed for repeatable professional system deployment.

Deployment Options

01

Main line-array deployment

Build scalable vertical arrays for professional sound reinforcement.

02

Coverage shaping

Use the product family and array geometry to match venue coverage requirements.

03

Rigging workflow

Confirm rigging, stacking and transport components with YL before use.

04

System integration

Combine with compatible subwoofers, controllers and cable accessories as required.



Rigging Components



K3-BUMP

Flying frame for K3 (incl. 1 BPCHAIN 1.5T)



K3-BAR

Extension bar for K3-BUMP



K3-RIGBAR

Rigging bar and pullback for K3 (includes LA-SLING2T)



K3-TILT

Rigging element for stacking K3 on KS28



DELTA 1.5T

Azimuth angle tuning accessory 1.5T



BPCHAIN 1.5T

Extension sling 1.5 tons

Transport & Cable Accessories



LA-SLING2T

1m chain sling with two-leg bridles rated 2 tons



KARA-DOWNK3

Interface for flying Kara (II) below K3




K3-CHARIOT

Chariot for up to 4 K3



K2-JACK

4 tilt adjustment screw jacks + bar for K2-CHARIOT



K3-CHARIOTLID

Protective lid for K3-CHARIOT



K3-CHARIOTCOV

Protective cover for 4 K3 on K3-CHARIOT



K3-BUMPFLIGHT

Modular flight case for 1 K3-BUMP and rigging elements



LASER-MAGPLATE

Magnetic plate for laser inclinometer
Confirm fitment with YL



SP25

Speaker cable: 4 x 4mm² NL4 25m length